

PRO 3216A

Acrylic Double Coated Black Foam



Technical Data Sheet

Pro 3216A is a double-coated black foam tape

developed for general purpose bonding applications.

Features & Benefits:

Adhesion bonds to most surfaces including low energy materials such as polyethylene and polypropylene.

1/16" foam carrier provides a gap filling function that aids in the joining of uneven or irregular surfaces.

Good UV resistance.

Excellent quick stick.

Moderate shear strength.

Technical Data

- ⇒ Liner: 5 mil High Density Blue Plastic Liner
- ⇒ Foam: Cross-linked Polyethylene
- ⇒ Adhesive: Acrylic
- ⇒ Thickness: 1/16" or 66 mils
- ⇒ Density: 4 lbs
- ⇒ Service Temperature: -30°F—220°F
- ⇒ Color: Black
- ⇒ Complies with AAMA 810.1-92 for glazing

Application:

Pro 3216A is a double-coated foam tape developed for general purpose bonding applications and window glazing. Pro 3216A is used for mounting nameplates, signs, small die cast parts, mirrors, maps, etc. Pro 3216A can also be used for sound and vibration dampening in business machines, industrial equipment, electronic component and packaging and glass panel mounts, seals and gaskets. The acrylic adhesive is recommended for outdoor applications due to its higher temperature, UV, weather, chemical and plasticizer resistance.

ISO 9001-2008
Certified



621 Route One South. North Brunswick, NJ 08902

Toll Free #1-800-345-0234

sales@protapes.com