

Shurtape P743 Black Photo Tape



Technical Data Sheet

Shurtape P743 is a opaque, matte surface...

“the photographer’s masking tape!”

Features & Benefits:

Hand tearable

High conformability

Easy, consistent unwind

High quick stick adhesion

An opaque black, matte finish surface insures the light free masking required for high quality photo reproduction

Technical Data

- ⇒ Backing: Impregnated paper
- ⇒ Adhesive: Synthetic rubber
- ⇒ Total tape thickness: 7 mils
- ⇒ Tensile strength: 24 lbs. per inch
- ⇒ Unwind @ 150 FPM: 25 oz. per inch
- ⇒ Adhesion to steel: 47 oz. per inch
- ⇒ Elongation: 8%
- ⇒ Service Temperature: 45°F to 150°F
- ⇒ Specifications: ASTM D6123/D6123M-97 (2012), Type 1

Application:

Shurtape P743 is engineered for quality photographic reproduction work—cropping and edging negatives; positioning negatives for contact printing; sealing camera bellows and film holders against light leaks.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902

Toll Free #1-800-345-0234

sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.