

# Shurtape Professional Grade P672 Gaff Tape



## Technical Data Sheet

**Shurtape Professional Grade P672 Gaff Tape is a highly versatile and popular matte surface cloth tape.**

### **Features & Benefits:**

Easy hand tear

Outstanding conformability to odd shaped and irregular surfaces

Provides a positive, waterproof and dirt resistant seal, yet permits easy clean removal

Performs well over a wide range of temperatures, both indoors & outdoors

Excellent abrasion resistance provides long life in high traffic areas

Colors: Black, White, Grey Olive Drab

### **Technical Data**

- ⇒ Backing: Impregnated cotton cloth
- ⇒ Adhesive: Synthetic Rubber
- ⇒ Unwind @ 150 FPM: 20 oz. per inch
- ⇒ Thickness: 12.0 mils
- ⇒ Adhesion to steel: 60 oz. per inch
- ⇒ Tensile strength: 69 lbs. per inch

### **Application:**

Shurtape Professional Grade P672 Gaffers tape is widely used in the Arts & Entertainment industry for holding and sealing applications. Shurtape Professional Grade Gaffers tape is used for the temporary mounting of lighting fixtures and reflectors; for the moisture and dustproof sealing of equipment cases and film containers; for bundling and positioning of floor cables; and floor marks for actor's positioning. Professional Grade Gaffers tape is preferred by photographers, cameraman and grips whenever an extra strong, waterproof and easy to use tape is needed.

ISO 9001  
Certified



621 Route One South. North Brunswick, NJ 08902

Toll Free #1-800-345-0234

[sales@protapes.com](mailto:sales@protapes.com)

*Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.*